

Catalyst Systems, Inc.

Catalyst Systems, Inc.
P.O. Box 88
2290 Zimmerman Road
Gnadenhutzen, OH 44629-0088

Phone: (740) 254-4311
FAX: (740) 254-9400
email:

PRODUCT DATA SHEET

50% DIBENZOYL PEROXIDE PASTE

DESCRIPTION:

A finely divided, non-separating, consistently smooth Benzoyl Peroxide paste in a **non-phthalate plasticizer** system.

APPLICATION:

Polymerization initiator, catalyst, or hardener for unsaturated polyester resin systems and vinyl monomer systems such as auto body fillers and boat repair/building compounds.

TYPICAL PROPERTIES:

ASSAY	(Typical assay is 49.0-50.0%)	47.5-50.0%
ACTIVE OXYGEN		3.3%
FORM		Smooth non-separating paste
COLOR		Red, Blue, Green, Raspberry, White (unpigmented)
VISCOSITY	(Typical, 100,000-120,000 cps)	120,000 cps @ 25° C ± 25,000 cps
SADT		54° C

(Paste physical properties, such as assay, viscosity, color, etc., can be formulated to meet individual customer requirements.)

PACKAGING:

Bulk 380 pound drums or custom packaging such as; squeeze tubes (0.5-4.0 OZ), pails (45 lb/pail), batch size pre-weighs, etc..

ISSUED: January 26, 2009
SUPERSEDES: 5/18/2000